



ZHEJIANG JINDA MEMBRANE TECHNOLOGY CO.,LTD.

PRODUCT: NOVA MEMBRANE STRUCTURE TYPE4

Item	Test method	Unit	Test value
Support Cloth	DIN ISO 2076		100%PES
Total Weight	DIN EN ISO 2286-2	g/m ²	1350
Composition Fabric	DIN EN ISO 2286-2	g/m ²	340
Composition Coating		g/m ²	1010
Width	DIN EN ISO 2286-1	cm	300
Thickness	DIN EN ISO 2286-2	mm	1.08
Tensile strength Warp	DIN 53354	N/5cm	7500
Tensile strength Weft	DIN 53354	N/5cm	7000
Tear strength Warp	DIN 53363	N	900
Tear strength Weft	DIN 53363	N	800
Adhesion Strength	DIN 53357	N/5cm	180
Temperature Resistance	BS 3424 Method 10		-40°C /+70°C
Folding Resistance	DIN53359 A		200,000T-NO CRACKS
Light fastness	DIN EN ISO 105 B02		>6
Elongation 24 h -10 daN/5 cm (warp/weft)	EN 15977		<1.2% / <1.2%
Residual elongation	EN 15977		<0.5% / <0.5%
Flame Retardant	B, s2 -d0		
Lacquering (optional)	Tio ₂ ,PVDF ,Acrylic		
Application	Arch-Membranes		

These indicated technical data are based on average results. actual data 's tolerance +-5%.Due to production procedures slight deviations can occur.All technical data are in accordance with the present standard of knowledge and give product information without legal binding.All data apply to new products

COMPANY: ZHEJIANG JINDA MEMBRANE TECHNOLOGY CO.,LTD.

ADD: NO.51 HONGQI ROAD,MAQIAO,HAINING,ZHEJIANG.CHINA. 314413